

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)														
		SW	OD					MIXED APPLICATION					CYCLIC*									
								mm/in	mm/in	static	10	20	25 to 65	70	bar	30						
IF710/ 75R42 CFO	DW25B DW23B DW24B	715	2133	944	6306	176D	speed symbol	bar	static	6	12	15 to 40	43	psi	19							
								10880								5910	4850	4730	4300	1.6	6620	
								12								23960	13020	10680	10420	9470	23	14580
								1.0								12400	6740	5520	5390	4900	1.8	7550
								15								27310	14850	12160	11870	10790	26	16630
								1.2								13800	7500	6150	6000	5460	2	8400
								17								30400	16520	13550	13220	12030	29	18500
								1.6								16330	8880	7280	7100	6460	2.4	9940
23	35970	19560	16040	15640	14230	35	21890															

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards