

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
IF600/ 70R30	DW20L DW21L	603 23.7	1602 63.1	726 28.6	4781 188.2	165D	0.8	6230	3390	2780	2710	2470	1.6	3790	
							12	13720	7470	6120	5970	5440	23	8350	
							1.2	7890	4290	3520	3430	3120	2	4800	
							17	17380	9450	7750	7560	6870	29	10570	
							1.6	9340	5080	4160	4060	3690	2.4	5680	
							23	20570	11190	9160	8940	8130	35	12510	
							2	10650	5790	4750	4630	4210	2.8	6480	
							29	23460	12750	10460	10200	9270	41	14270	
							2.4	11850	6440	5280	5150	4690	3.2	7210	
35	26100	14190	11630	11340	10330	46	15880								

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards