

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF520/ 85R42	DW18L	536 21.1	1955 77.0	863 34.0	5804 228.5	174D	0.8	7410	3450	3220	3220	2930	1.6	4510	
							12	16320	7600	7090	7090	6450	23	9930	
							1.2	9380	4370	4080	4080	3710	2	5710	
							17	20660	9630	8990	8990	8170	29	12580	
							1.6	11110	5180	4830	4830	4400	2.4	6760	
							23	24470	11410	10640	10640	9690	35	14890	
							1.8	11890	5540	5170	5170	4700	2.6	7240	
							26	26190	12200	11390	11390	10350	38	15950	
							2.8	15410	7180	6700	6700	6100	3.6	9380	
41	33940	15810	14760	14760	13440	52	20660								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards