

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar	static	10	20	25 to 65
VF800/ 70R38	DW27B DW28B DW30B	810 28.3	2085 77.1	898 33.5	6124 228.3	187D	0.8	11800	5500	5130	5130	4670	1.6	7180	
							12	25990	12110	11300	11300	10290	23	15810	
							1.2	14950	6960	6500	6500	5920	2	9100	
							17	32930	15330	14320	14320	13040	29	20040	
							1.6	17690	8240	7690	7690	7000	2.4	10770	
							23	38960	18150	16940	16940	15420	35	23720	
							2	20150	9390	8760	8760	7970	2.8	12260	
							29	44380	20680	19300	19300	17560	41	27000	
							2.4	22430	10450	9750	9750	8870	3.2	13650	
35	49410	23020	21480	21480	19540	46	30070								

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards