

# LOADPRO



**FEATURE**

Greater lug overlap and more lugs in footprint

**BENEFIT**

Uniform load distribution

**FEATURE**

Extra reinforced Sidewalls

**BENEFIT**

Additional lateral stability


**FEATURE**

Strong bead

**BENEFIT**

Better carcass strength and load carrying capacity

## MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius	mm	Speed		Constant load					Cyclic operation		
		mm	mm	mm	mm	bar		10	20	30	40	50	10	15	
		in	in	in	in	psi		6	12	19	25	31	6	9	
440/ 80R24	W14L	441	1314	591	3922	161 A8/B	1.6	6230	3390	2950	2820	2710	2710	4070	3630
							23	13720	7470	6500	6210	5970	5970	8960	8000
	W15L						2.2	7500	4080	3550	3390	3260	3260	4890	4370
							32	16520	8990	7820	7470	7180	7180	10770	9630
	W16L						3.0	8990	4890	4260	4070	3910	3910	5870	5240
							44	19800	10770	9380	8960	8610	8610	12930	11540
							4	10640	5780	5040	4810	4625	4625	6940	6200
							58	23440	12730	11100	10590	10190	10190	15290	13660