

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)							
		SW	OD	Radius	mm	Speed			Constant load					Cyclic operation		
		mm	mm	mm	mm	bar			10	20	30	40	50	10	15	
		in	in	in	in	psi			6	12	19	25	31	6	9	
480/ 80R26	W15L	503	1428	636	4262	160 A8/B	1.6	6900	3750	3270	3120	3000	3000	4500	4020	
							23	15200	8260	7200	6870	6610	6610	9910	8850	
	2.2						8300	4510	3930	3750	3610	3610	5420	4840		
	32						18280	9930	8660	8260	7950	7950	11940	10660		
	2.8						9570	5200	4530	4330	4160	4160	6240	5570		
	41						21080	11450	9980	9540	9160	9160	13740	12270		
	3.2						10350	5630	4910	4680	4500	4500	6750	6030		
	46						22800	12400	10810	10310	9910	9910	14870	13280		