

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Speed Radius Index (SRI)	Load Index Speed Symbol	Infl. Press.	Maximum load, kg (lbs) Speed, km/h (mph)						
			SW	OD						MIXED APPLICATION				CYCLIC*		
			mm/in	mm/in						10	20	25 to 65 km/h 15 to 40 mph	70	bar	10	
										6	12		43	psi	6	
VF 900/ 60R38	DW30B	TL	891 35.1	2040 80.3	881 34.7	6024 237.2	975	193D	0.8	12720	5930	5530	5530	5030	1.6	7740
									12	28020	13060	12180	12180	11080	23	17050
									1.2	16120	7510	7010	7010	6380	2	9810
									17	35510	16540	15440	15440	14050	29	21610
									1.6	19070	8880	8290	8290	7540	2.4	11610
									23	42000	19560	18260	18260	16610	35	25570
									2.4	24170	11260	10510	10510	9560	3.2	14710
									35	53240	24800	23150	23150	21060	46	32400
									2.8	26450	12320	11500	11500	10470	3.6	16100
									41	58260	27140	25330	25330	23060	52	35460

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards