

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
520/85R42	169A8/B	TL	DW16L DW18L	530 20.87	1951 76.81	889 35	5791 228	1	6510	4250	3480	3030	2830	2830
								15	14340	9360	7670	6670	6230	6230
								2	9780	6380	5230	4550	4250	4250
								29	21540	14050	11520	10020	9360	9360
								2.8	11910	7770	6370	5540	5180	5180
								41	26230	17110	14030	12200	11410	11410
								3.4	13340	8700	7130	6210	5800	5800
								49	29380	19160	15700	13680	12780	12780