

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	ΠŪ	IIII. FI633	Static	10	20	30	40	50
									otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	meconiniena toda kg/fbs					
340/85R36	132 A8/B	Ħ						0.8	3060	2000	1640	1420	1330	1330
								12	6740	4410	3610	3130	2930	2930
								1	3500	2280	1870	1630	1520	1520
			W12	355	1492	694	4485	15	7710	5020	4120	3590	3350	3350
			W11	14	58.7	27.3	176.6	1.3	4070	2660	2180	1890	1770	1770
								19	8960	5860	4800	4160	3900	3900
								1.6	4600	3000	2460	2140	2000	2000
								23	10130	6610	5420	4710	4410	4410

All tires confirms ETRTO T&RA & STRO standards