

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	nυ	IIII. FI633	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi						
420/85R30	140 A8/B	Ħ	W15L W14L W13	450 17.7	1476 58.1	673 26.5	4385 172.6	0.8	3840	2510	2050	1790	1670	1670
								12	8460	5530	4520	3940	3680	3680
								1	4370	2850	2340	2030	1900	1900
								15	9630	6280	5150	4470	4190	4190
								1.3	5080	3320	2720	2360	2210	2210
								19	11190	7310	5990	5200	4870	4870
								1.6	5750	3750	3080	2680	2500	2500
								23	12670	8260	6780	5900	5510	5510

All tires confirms ETRTO T&RA & STRO standards