

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance

FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	ΝŪ	IIII. FIGSS	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	ricoommena toda kg/ibs					
380/85R24	131 A8/B	F	W12 W13 W11	385	1260	571	3728	0.8	2990	1950	1600	1390	1300	1300
								12	6590	4300	3520	3060	2860	2860
								1	3400	2220	1820	1580	1480	1480
								15	7490	4890	4010	3480	3260	3260
				15.2	49.6	22.5	146.8	1.3	3980	2600	2130	1850	1730	1730
								19	8770	5730	4690	4070	3810	3810
								1.6	4490	2930	2400	2090	1950	1950
								23	9890	6450	5290	4600	4300	4300

All tires confirms ETRTO T&RA & STRO standards