

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	oln .	nυ	IIIII. FIESS	Static	10	20	30	40	50
									0	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	necommend toda ky / ibs					
250/85R24	109 A8/B	F	W8 W7 W9	250 9.8	1036 40.8	477 18.8	3097 121.9	0.8	1590	1040	850	740	690	690
								12	3500	2290	1870	1630	1520	1520
								1	1790	1170	960	830	780	780
								15	3940	2580	2110	1830	1720	1720
								1.3	2090	1370	1120	970	910	910
								19	4600	3020	2470	2140	2000	2000
								1.6	2370	1550	1270	1100	1030	1030
								23	5220	3410	2800	2420	2270	2270

All tires confirms ETRTO T&RA & STRO standards