

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
650/65R38	163D	TL	DW20B	645	1811	825	5489	1.4	4080	4210	3890	3730	3550	1.75	6040	5500
								20	8990	9270	8570	8220	7820	25	13300	12110
								1.6	4420	4550	4200	4030	3840	2	6530	5950
								23	9740	10020	9250	8880	8460	29	14380	13110
								2	5040	5190	4800	4600	4380	2.5	7450	6790
								29	11100	11430	10570	10130	9650	36	16410	14960
								2.4	5610	5780	5340	5120	4875	3	8290	7560
35	12360	12730	11760	11280	10740	44	18260	16650								

All tires confirms ETRTO T&RA & STRO standards