

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
540/65R34	145D	TL	W16L W18L	550 21.7	1566 61.7	717 28	4659 183.4	0.8	2220	2290	2110	2030	1930	1	3280	2990
								12	4890	5040	4650	4470	4250	15	7220	6590
								1	2530	2610	2410	2310	2200	1.25	3740	3410
								15	5570	5750	5310	5090	4850	18	8240	7510
								1.3	2960	3050	2810	2700	2570	263	4370	3980
								19	6520	6720	6190	5950	5660	3811	9630	8770
								1.6	3340	3440	3180	3050	2900	2	4930	4500
								23	7360	7580	7000	6720	6390	29	10860	9910

All tires confirms ETRTO T&RA & STRO standards