

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
600/65R30	149D	TL	DW20B W18L	611 24.1	1542 60.7	693 27	4626 182	0.8	2500	2570	2380	2280	2170	1	3690	3360
								12	5510	5660	5240	5020	4780	15	8130	7400
								1	2840	2930	2700	2590	2470	1.25	4200	3830
								15	6260	6450	5950	5700	5440	18	9250	8440
								1.3	3310	3410	3150	3020	2880	1.63	4900	4460
								19	7290	7510	6940	6650	6340	24	10790	9820
								1.6	3740	3850	3560	3410	3250	2	5530	5040
								23	8240	8480	7840	7510	7160	29	12180	11100

All tires confirms ETRTO T&RA & STRO standards