

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
									25	40	50	65	bar	10	15	
				mm	mm				16	25	31	40	psi	6	9	
in	in	Recommend load kg / lbs														
600/65R28	154D	TL	DW20B W18L	591	1491	668	4473	1.8	3650	3760	3470	3330	3170	2.25	5390	4910
								26	8040	8280	7640	7330	6980	33	11870	10810
								2	3880	3990	3690	3540	3370	2.5	5730	5220
								29	8550	8790	8130	7800	7420	36	12620	11500
								2.2	4090	4220	3900	3740	3560	2.75	6050	5520
								32	9010	9300	8590	8240	7840	40	13330	12160
								2.4	4310	4440	4110	3940	3750	3	6380	5810
								35	9490	9780	9050	8680	8260	44	14050	12800