

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

| Size      | LI/SS | Type | Rim          | Unloaded Dimension |              | SLR       | RC            | Infl. Press | Speed kmph / mph     |      |      |      |                  |      |      |      |
|-----------|-------|------|--------------|--------------------|--------------|-----------|---------------|-------------|----------------------|------|------|------|------------------|------|------|------|
|           |       |      |              | SW                 | OD           |           |               |             | Non cyclic operation |      |      |      | Cyclic operation |      |      |      |
|           |       |      |              | mm                 | mm           |           |               |             | Static               | 25   | 40   | 50   | 65               | bar  | 10   | 15   |
|           |       |      |              | in                 | in           |           |               |             | 16                   | 25   | 31   | 40   | psi              | 6    | 9    |      |
| 480/65R24 | 140D  | TL   | W15L<br>W14L | 480<br>18.9        | 1234<br>48.6 | 558<br>22 | 3644<br>143.5 | 1.8         | 2440                 | 2510 | 2320 | 2230 | 2120             | 2.25 | 3600 | 3290 |
|           |       |      |              |                    |              |           |               | 26          | 5370                 | 5530 | 5110 | 4910 | 4670             | 33   | 7930 | 7250 |
|           |       |      |              |                    |              |           |               | 2           | 2590                 | 2670 | 2460 | 2360 | 2250             | 2.5  | 3830 | 3490 |
|           |       |      |              |                    |              |           |               | 29          | 5700                 | 5880 | 5420 | 5200 | 4960             | 36   | 8440 | 7690 |
|           |       |      |              |                    |              |           |               | 2.2         | 2740                 | 2820 | 2610 | 2500 | 2380             | 2.75 | 4050 | 3690 |
|           |       |      |              |                    |              |           |               | 32          | 6040                 | 6210 | 5750 | 5510 | 5240             | 40   | 8920 | 8130 |
|           |       |      |              |                    |              |           |               | 2.4         | 2880                 | 2960 | 2740 | 2630 | 2500             | 3    | 4250 | 3880 |
|           |       |      |              |                    |              |           |               | 35          | 6340                 | 6520 | 6040 | 5790 | 5510             | 44   | 9360 | 8550 |

All tires confirms ETRTO T&RA & STRO standards