

# T422 VALUE PRO



**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced damage to crops


**FEATURE**

- Larger volume and footprint

**BENEFIT**

- Reduced compaction

## MACHINERY



Trailer

| Size        | LI/SS         |               | PR | Type | Rim     | Unloaded dimension |      | SLR | RC   | Infl. pressure | Load capacity |              |             |     |     |
|-------------|---------------|---------------|----|------|---------|--------------------|------|-----|------|----------------|---------------|--------------|-------------|-----|-----|
|             | Free Rolling  | Drive Wheel   |    |      |         | SW                 | OD   |     |      |                | Max Speed     | Free Rolling | Drive Wheel |     |     |
|             |               |               |    |      |         | mm                 | mm   |     |      |                |               |              |             | kg  | kg  |
|             |               |               |    |      |         | in                 | in   |     |      |                |               |              |             | lbs | lbs |
| 500/60-22.5 | 163 A8/ 159 B | 151 A8/ 148 B | 16 | TL   | 16.00DC | 500                | 1170 | 510 | 3490 | 3.2            | 40            | 4875         | 3450        |     |     |
|             |               |               |    |      |         | 20                 | 46   | 20  | 137  | 46             | 25            | 10750        | 7605        |     |     |

Also available in sizes: 550/45-22.5, 550/60-22.5, 400/55-22.5, 500/ 45-22.5

All tires confirms ETRTO T&RA & STRO standards