FARMAX R85 AG RADIAL

WITH THE POWER OF CTR*

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- Rounded shoulder

BENEFIT
- Lesser damage to soil and crop

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

FEATURE
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

LIST OF SIZES

SIZE	LI/SI	SIZE	LI/SI
250/85 R 20	116 A8/B	320/85 R 32	142 A8/B
280/85 R 20	112 A8/B	320/85 R 32	145 A8/B
320/85 R 20	119 A8/B	320/85 R 34	141 A8/B
250/85 R 24	109 A8/B	380/85 R 34	137 A8/B
280/85 R 24	115 A8/B	420/85 R 34	142 A8/B
320/85 R 24	122 A8/B	420/85 R 34	142 D
320/85 R 24	142 A8/B	420/85 R 34	145 A8
340/85 R 24	125 A8/B	420/85 R 34	147 A8/B
340/85 R 24	125 D	460/85 R 34	147 A8/B
340/85 R 24	128 A8	460/85 R 34	157 A8/B
380/80 R 38	154 D	320/85 R 36	128 A8/B
380/80 R 38	157 A8	340/85 R 36	132 A8/B
380/85 R 24	131 A8/B	320/85 R 38	143 A8/B
380/85 R 24	131 D	340/85 R 38	133 A8/B
380/85 R 24	134 A8	340/85 R 38	148 A8/B
420/85 R 24	137 A8/B	340/85 R 38	151 A8/B
250/85 R 28	112 A8/B	420/85 R 38	144 A8/B
280/85 R 28	118 A8/B	460/85 R 38	149 A8/B
320/85 R 28	124 A8/B	460/85 R 38	153 A8/B
340/85 R 28	127 A8/B	460/85 R 38	167 A8/B
380/85 R 28	133 A8/B	520/85 R 38	169 A8/B
380/85 R 28	133 D	520/85 R 38	155 A8/B
380/85 R 28	136 A8	520/85 R 42	157 A8/B
420/85 R 28	139 A8/B	520/85 R 42	169 A8/B
380/85 R 30	135 A8/B	520/85 R 42	169 D
420/85 R 30	140 A8/B	520/85 R 42	172 A8
420/85 R 30	140 D	340/85 R 46	150 D
420/85 R 30	143 A8	340/85 R 46	153 A8
420/85 R 30	147 A8/B	520/85 R 46	158 A8/B
460/85 R 30	145 A8/B	520/85 R 46	174 A8/B
320/85 R 32	126 A8/B	420/90 R 30	142 A8/B

All tyres conform to ETRTO & TRA standards. Sizes available as of 02/2022.