

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar psi	10	15
650/ 65R42	165D	TL	W18, DW20BL DW21B	645	1913	885	5775	0.8	3250	3350	3100	2970	2830	1	4810	4390
								12	7160	7380	6830	6540	6230	15	10590	9670
								1.3	4320	4460	4120	3950	3760	1.6	6390	5830
								1.9	9520	9820	9070	8700	8280	2.4	14070	12840
								1.8	4990	5140	4750	4560	4340	2.25	7380	6730
								2.6	10990	11320	10460	10040	9560	33	16260	14820
								2.4	5920	6100	5640	5410	5150	3	8760	7980
								3.5	13040	13440	12420	11920	11340	44	19300	17580

All tires confirms ETRTO T&RA & STRO standards