

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
280/85R24	115 A8/ 115 B	TL	W10 W9	285 11.2	1086 42.8	498 19.6	3235 127.4	0.8	1860	1220	1000	870	810	810
								12	4100	2690	2200	1920	1780	1780
								1	2120	1380	1130	980	920	920
								15	4670	3040	2490	2160	2030	2030
								1.3	2480	1620	1330	1160	1080	1080
								19	5460	3570	2930	2560	2380	2380
								1.6	2790	1820	1490	1300	1215	1215
								23	6150	4010	3280	2860	2680	2680