

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
650/65R42	165D	TL	DW20B W18L	645 25.4	1913 75.3	885 34.8	5778 227.5	1.8	4990	5140	4750	4560	4340	2.25	7380	6730
								26	10990	11320	10460	10040	9560	33	16260	14820
								2	5310	5470	5060	4850	4620	2.5	7850	7160
								29	11700	12050	11150	10680	10180	36	17290	15770
								2.2	5620	5790	5350	5130	4890	2.75	8310	7580
								32	12380	12750	11780	11300	10770	40	18300	16700
								2.4	5920	6100	5640	5410	5150	3	8760	7980
35	13040	13440	12420	11920	11340	44	19300	17580								