

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm in	mm in					mm in	mm in	bar psi	6	16	25
270/95R32 (11.2R32)	133D/ 136A8	TL	W8 W9 W10	275 10.8	1327 52.2	613 24.1	4002 157.6	2.8	1920	2510	1980	1830	1750	1670	1520
								41	4230	5530	4360	4030	3850	3680	3350
								3.6	2230	2910	2300	2120	2040	1940	1770
								52	4910	6410	5070	4670	4490	4270	3900
								4	2370	3090	2440	2260	2160	2060	1870
58	5220	6810	5370	4980	4760	4540	4120								

All tires confirms ETRTO T&RA & STRO standards