

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm in	mm in					6	16	25	31	40	50
340/85R46	147D/ 150A8	TL	W11 W12	343 13.5	1746 68.7	816 32.1	5310 209	2.8	3050	3980	3140	2900	2780	2650	2410
								41	6720	8770	6920	6390	6120	5840	5310
								3.2	3300	4310	3400	3140	3010	2870	2610
								46	7270	9490	7490	6920	6630	6320	5750
								3.6	3540	4610	3640	3370	3230	3075	2800
								52	7800	10150	8020	7420	7110	6770	6170

All tires confirms ETRTO T&RA & STRO standards