

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

| Size | LI/SS | Type | Rim | Unloaded Dimension | | SLR | RC | Infl. Press | Speed kmph / mph | | | | | | | |
|--------------------------|------------|------|-----------|--------------------|--------------|-------------|-------------|-------------|------------------------|------|------|------|------|------|------|----|
| | | | | SW | OD | | | | Field | | 10 | 25 | 40 | 50 | 65 | 70 |
| | | | | mm | mm | | | | 6 | 16 | 25 | 31 | 40 | 50 | | |
| | | | | in | in | | | | Recommend load kg /lbs | | | | | | | |
| 300/95R46 (12.4 R 46) | 143D/146A8 | TL | W9 W10 | 300 11.8 | 1738 68.4 | 817 32.1 | 5155 203 | 2.4 | 2470 | 3230 | 2550 | 2370 | 2260 | 2150 | 1960 | |
| | | | | | | | | 35 | 5440 | 7110 | 5620 | 5220 | 4980 | 4740 | 4320 | |
| | | | | | | | | 2.8 | 2700 | 3530 | 2780 | 2590 | 2470 | 2350 | 2140 | |
| | | | | | | | | 41 | 5950 | 7780 | 6120 | 5700 | 5440 | 5180 | 4710 | |
| | | | | | | | | 3.2 | 2920 | 3810 | 3010 | 2790 | 2670 | 2540 | 2310 | |
| | | | | | | | | 46 | 6430 | 8390 | 6630 | 6150 | 5880 | 5590 | 5090 | |
| | | | | | | | | 3.6 | 3130 | 4090 | 3230 | 3000 | 2860 | 2725 | 2480 | |
| | | | | | | | | 52 | 6890 | 9010 | 7110 | 6610 | 6300 | 6000 | 5460 | |