

TORQUEMAX AG RADIAL

CEAT
SPECIALTY

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures



LIST OF SIZES

SIZE	LI/SI
IF 520/85 R38	167 D
IF 600/70 R30	165 D
IF 600/70 R34	160 D
IF 600/70 R34	167 D
IF 650/60 R34	159 D
IF 710/70 R38 CFO	178 D
IF 710/70 R38 CFO	181A8/B
IF 710/70 R42	179 D
IF 710/75 R42 CFO	176 D
IF 710/75 R42 CFO	179 D
VF 520/85 R38	170 D
VF 520/85 R42	174 D/ 177 A8
VF 540/65 R30 NRO	158 D
VF 600/65 R28	163 D
VF 600/60 R28 NRO	157 D
VF 600/70 R30	170 D
VF 600/70 R30 SB*	170 D
VF 650/65 R34 SB*	167 D
VF 650/60 R34	168 D
VF 650/60 R34 SB*	168 D
VF 650/65 R34 SB*	170 D
VF 650/60 R42 SB*	174 D
VF 650/65 R34	167 D
VF 650/65 R34	170 D
VF 650/65 R42 NRO	174 D
VF 710/60 R38 NRO	171 D
VF 710/70 R38 CFO	178 D
VF 710/70 R42 CFO	185 D
VF 710/70 R42 SB*	185 D
VF 710/75 R42 CFO	184 D
VF 710/75 R42 SB*	184 D
VF 800/70 R38	187 D
VF 800/70 R38 SB*	187 D
VF 800/70 R42 SB*	187 D

* SB - Steel belted

All tyres conform to ETRTO & TRA standards. Sizes available as of 8/2022.