

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)							
			SW	OD				Non cyclic operation				Cyclic operation			
								Static	25	40	50	65	bar	10	15
			mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	psi	Recommend load, kg (lbs)		
340/65R20	124D	W11 W10 W12	343 13.5	950 37.4	431 17	2850 112	1.8	1550	1600	1480	1420	1350	2.25	2300	2090
							26	3410	3520	3260	3130	2970	33	5070	4600
							2	1660	1710	1580	1510	1440	2.5	2450	2230
							29	3660	3770	3480	3330	3170	36	5400	4910
							2.2	1750	1800	1660	1600	1520	2.75	2580	2360
							32	3850	3960	3660	3520	3350	40	5680	5200
							2.4	1840	1900	1750	1680	1600	3	2720	2480
							35	4050	4190	3850	3700	3520	44	5990	5460

All tires confirms ETRTO T&RA & STRO standards