

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)							
			SW	OD				Non cyclic operation					Cyclic operation		
								mm/in	mm/in	bar	25	40	50	65	bar
			psi	16											
650/65R42	170D	DW20B W18L	645 25.4	1913 75.3	885 34.8	5775 227.4	2.4	5840	6020	5560	5330	5080	3	8640	7870
							35	12860	13260	12250	11740	11190	44	19030	17330
							2.8	6390	6590	6090	5840	5560	3.5	9450	8620
							41	14070	14520	13410	12860	12250	51	20810	18990
							3	6660	6860	6340	6080	5790	3.75	9840	8970
							44	14670	15110	13960	13390	12750	54	21670	19760
							3.2	6900	7110	6570	6300	6000	3.9875	10200	9300
							46	15200	15660	14470	13880	13220	58	22470	20480

All tires confirms ETRTO T&RA & STRO standards