

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)						
			SW	OD				Static	10	25	40	50	65	70
			mm/in	mm/in					6	15	25	31	40	43
710/70R38	178D/181A8	DW 23 B DW 25 B	715 28.1	1959 77.1	887 34.7	5785 227.8	2.6	15270	9960	7870	7270	6970	6640	6040
							38	33630	21940	17330	16010	15350	14630	13300
							2.8	15940	10400	8210	7590	7280	6930	6310
							41	35110	22910	18080	16720	16040	15260	13900
							3	16610	10830	8560	7910	7580	7220	6570
							44	36590	23850	18850	17420	16700	15900	14470
							3.2	17250	11250	8890	8210	7880	7500	6830
							46	38000	24780	19580	18080	17360	16520	15040