

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm / in	mm / in					Field	10	25	40	50	65	70
270/95R54 (11.2R54)	W9 W8 W10	275 10.8	1886 74.3	892 35.1	5783 227.7	146D/149A8	0.8	620	810	640	590	570	540	490
							12	1370	1780	1410	1300	1260	1190	1080
							1.2	780	1020	810	740	710	680	620
							17	1720	2250	1780	1630	1560	1500	1370
							1.6	930	1220	960	890	850	810	740
							23	2050	2690	2110	1960	1870	1780	1630
							2.2	2430	3170	2500	2310	2220	2110	1920
							32	5350	6980	5510	5090	4890	4650	4230
							2.8	2790	3650	2880	2660	2550	2430	2210
							41	6150	8040	6340	5860	5620	5350	4870
							3.2	3020	3950	3120	2880	2760	2630	2390
							46	6650	8700	6870	6340	6080	5790	5260
							3.5	3190	4160	3280	3030	2910	2770	2520
							51	7030	9160	7220	6670	6410	6100	5550
4	3450	4500	3560	3290	3150	3000	2730							
58	7600	9910	7840	7250	6940	6610	6010							

All tires confirms ETRTO T&RA & STRO standards