

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)					
				SW	OD				Speed, km/h (mph)					
				mm/in	mm/in				mm/in	10	20	30	40	50
										6	12	19	25	31
480/70R34	155 A8/B	TL	W14L W15L W16L	490	1580	722	4698	0.8	4160	2720	2230	1940	1810	1810
								12	9160	5990	4910	4270	3990	3990
								1.3	5540	3620	2960	2580	2410	2410
								19	12200	7970	6520	5680	5310	5310
								1.6	6270	4090	3350	2920	2725	2730
								23	13810	9010	7380	6430	6000	6010
								2.4	7480	4880	3610	3480	3250	3250
								35	16480	10750	7950	7670	7160	7160
								2.6	8050	5250	4310	3750	3500	3500
								38	17730	11560	9490	8260	7710	7710
								2.8	8400	5480	4490	3910	3650	3650
								41	18500	12070	9890	8610	8040	8040
								3	8740	5700	4670	4070	3800	3800
								44	19250	12560	10290	8960	8370	8370
								3.1	8910	5810	4300	4150	3875	3875
45	19630	12800	9470	9140	8540	8540								

All tires confirms ETRTO T&RA & STRO standards