

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					10	20	30	40 to 65	70	15	30	
IF 710/ 70R42	DW23B DW25B	720 28.3	2061 81.1	930 36.6	6120 241.0	179D	speed	bar	10	20	30	40 to 65	70	15	30
							symbol	psi	6	12	19	25 to 40	43	9	19
							0.8	5180	4410	4240	4080	3710	4690	4470	
							12	11410	9710	9340	8990	8170	10330	9850	
							1.2	6570	5580	5380	5170	4700	5950	5660	
							17	14470	12290	11850	11390	10350	13110	12470	
							1.6	7770	6610	6360	6120	5570	7040	6700	
							23	17110	14560	14010	13480	12270	15510	14760	
							2.0	8850	7530	7250	6970	6340	8020	7630	
							29	19490	16590	15970	15350	13960	17670	16810	
							2.2	9360	7960	7660	7370	6710	8480	8070	
							32	20620	17530	16870	16230	14780	18680	17780	
2.4	9840	8370	8060	7750	7050	8910	8490								
35	21670	18440	17750	17070	15530	19630	18700								