FARMAX R70 AG RADIAL

WITH THE POWER OF CTR*

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

FEATURE
- Rounded shoulder

BENEFIT
- Reduced damage to soil and crop

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

*Lower Compaction, Higher Traction and Better Roadability

LIST OF SIZES

SIZE	LI/SS
260/70 R 20	113 A8/B
280/70 R 20	116 A8/B
300/70 R 20	110 A8/B
300/70 R 20	120 A8/B
320/70 R 20	113 A8/B
320/70 R 20	123 A8/B
360/70 R 20	120 A8/B
360/70 R 20	129 A8/B
380/70 R 20	122 A8/B
380/70 R 20	132 A8/B
320/70 R 24	116 A8/B
360/70 R 24	122 A8/B
380/70 R 24	125 A8/B
380/70 R 24	125 D
380/70 R 24	128 A8
420/70 R 24	130 A8/B
420/70 R 24	130 D
420/70 R 24	133 A8
480/70 R 24	138 A8/B
320/70 R 28	119 A8/B
360/70 R 28	125 A8/B
380/70 R 28	127 A8/B
420/70 R 28	133 A8/B
420/70 R 28	133 D
420/70 R 28	136 A8
480/70 R 28	140 A8/B
480/70 R 28	151 A8/B

SIZE	LI/SS
600/70 R 28	161 A8/B
420/70 R 30	134 A8/B
480/70 R 30	141 A8/B
480/70 R 30	147 D
480/70 R 30	150 A8
520/70 R 30	145 A8/B
600/70 R 30	152 A8/B
600/70 R 30	158 A8/B
480/70 R 34	143 A8/B
480/70 R 34	149 A8/B
480/70 R 34	155 A8/B
520/70 R 34	148 A8/B
480/70 R 38	145 A8/B
520/70 R 38	150 A8/B
580/70 R 38	155 A8/B
710/70 R 38	172 A8/B
710/70 R 38	178 A8/B
710/70 R 38	178 D
710/70 R 38	181 A8
580/70 R 42	158 A8/B
580/70 R 42	158 D
580/70 R 42	161 A8
620/70 R 42	166 A8/B
620/70 R 42	173 A8/B
710/70 R 42	173 A8/B
710/70 R 42	173 D
710/70 R 42	176A8

All tyres conform to ETRTO & TRA standards. Sizes available as of 09/2020.