

FARMAX R70

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in				mm/in	10	20	30	40	50	65
380/70R24	125 D/128A8	TL	W13 W12 W11	380	1190	540	3523	bar							
								psi	Static	6	12	19	25	31	40
								0.8	2530	1650	1350	1270	1200	1160	1100
								12	5570	3630	2970	2800	2420	2560	2420
								1	2880	1880	1540	1440	1370	1310	1250
								15	6340	4140	3390	3170	2750	2890	2750
								1.3	3360	2190	1800	1680	1600	1530	1460
								19	7400	4820	3960	3700	3220	3370	3220
1.6	3800	2480	2030	1900	1810	1730	1650								
23	8370	5460	4470	4190	3990	3810	3630								

All tires confirms ETRTO T&RA & STRO standards