RPG

FARMAX R70

CEAT SPECIALTY

FEATURE
- Higher angle and lug overlap at centre

BENEFIT
- Better roadability

FEATURE
- R1-W tread depth

BENEFIT
- Longer tyre life

FEATURE
- Wider tread
- Larger inner volume

BENEFIT
- Reduced soil compaction

FEATURE
- Rounded shoulder

BENEFIT
- Reduced damage to soil and crop

FEATURE
- Lower angle at shoulder

BENEFIT
- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum-ference	Infl.Press	Recommend load, kg (lbs)					
				SW	OD				Speed, km/h (mph)					
				mm/in	mm/in	mm/in	mm/in	bar	Static	10	20	30	40	50
								psi		6	12	19	25	31
580/ 70R38	180 A8/B	TL	W18L	577 22.7	1827 71.9	832 32.7	5420 213.4	4.6	16770	10940	8970	7800	7290	7290
								67	36940	24100	19760	17180	16060	16060
								5	17600	11480	8490	8190	7650	7650
								73	38770	25290	18700	18040	16850	16850
								5.4	18400	12000	8880	8560	8000	8000
								78	40530	26430	19560	18850	17620	17620

All tires confirms ETRTO T&RA & STRO standards