

FARMAX R70

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)							
				SW	OD				Speed, km/h (mph)							
				mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
280/70R16	112A8/B	TL	W8 W9 W10	282	798	360	2382	bar psi	Static	10	20	30	40	50		
										6	12	19	25	31		
										0.8	1360	890	730	630	590	590
										12	3000	1960	1610	1390	1300	1300
										1.4	1890	1230	1010	880	820	820
										20	4160	2710	2220	1940	1810	1810
										2	2320	1520	1240	1080	1010	1010
										29	5110	3350	2730	2380	2220	2220
2.4	2580	1680	1380	1200	1120	1120										
35	5680	3700	3040	2640	2470	2470										