

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability

FEATURE

Steel belted radial construction

BENEFIT

Protection from Punctures


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum.	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius				Constant load					Cyclic operation		
		mm	mm	mm	mm	Speed	bar	10	20	30	40	50	10	15	
		in	in	in	in	Symbol	psi	Static	6	12	19	25	31	6	9
480 80R26 SB*	W15L	479	1428	636	4262	160A8/B	1.6	6900	3750	3270	3120	3000	3000	4500	4020
							23	15200	8260	7200	6870	6610	43500	9910	8850
	2.2						8300	4510	3930	3750	3610	3610	5420	4840	
	32						18280	9930	8660	8260	7950	52345	11940	10660	
	2.8						9570	5200	4530	4330	4160	4160	6240	5570	
	41						21080	11450	9980	9540	9160	60320	13740	12270	
	3.2						10350	5630	4910	4680	4500	4500	6750	6030	
	46						22800	12400	10810	10310	9910	65250	14870	13280	
	W16L	18.9	56.2	25.0	168										
	W18L														

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards