

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi	static	Up to 65km/h Up to 40mph	70 43	10 6
VF 710/ 70R38 SB*	DW 23B, DW 25B	TL	720 28.3	1959 77.1	851 33.5	5754 228.3	178D	0.8	11500	5000	4550	7000
								12	25330	11010	10020	15420
								1	13110	5700	5190	7980
								15	28880	12560	11430	17580
								1.2	14580	6340	5770	8880
								17	32110	13960	12710	19560
								1.4	15960	6940	6320	9720
								20	35150	15290	13920	21410
								1.6	17250	7500	6830	10500
								23	38000	16520	15040	23130

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards