

# LOADPRO



**FEATURE**

Greater lug overlap and more lugs in footprint

**BENEFIT**

Uniform load distribution

**FEATURE**

Extra reinforced Sidewalls

**BENEFIT**

Additional lateral stability

**FEATURE**

Steel belted radial construction

**BENEFIT**

Protection from Punctures


**FEATURE**

Strong bead

**BENEFIT**

Better carcass strength and load carrying capacity

## MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)							
		Speed, km/h (mph)							Constant load				Cyclic operation			
		SW	OD	10	20	30	40		50	10	15					
		mm	mm	mm	mm	mm	mm		mm	mm	mm					
400 70R20 SB*	12SDC	404	1067	475	3184	149 A8/B	1.6	4370	2380	2070	1980	1900	1900	2850	2550	
	W13	15.9	42	18.7	125		23	9630	5240	4560	4360	4190	27550	6280	5620	
	W14L						2.2	5270	2860	2500	2380	2290	2290	3440	3070	
								32	11610	6300	5510	5240	5040	33205	7580	6760
								3.2	6560	3560	3110	2960	2850	2850	4280	3820
								46	14450	7840	6850	6520	6280	41325	9430	8410
								4	7480	4060	3540	3380	3250	3250	4880	4360
							58	16480	8940	7800	7440	7160	47125	10750	9600	

\* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards