

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability

FEATURE

Steel belted radial construction

BENEFIT

Protection from Punctures


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)						
		SW	OD						Speed, km/h (mph)						
									Constant load					Cyclic operation	
									10	20	30	40	50	10	15
mm	mm	mm	mm	mm	Speed	bar		6	12	19	25	31	6	9	
in	in	in	in	in	Symbol	psi									
440/ 80R28 SB*	W14L	441	1415	637	4223	156A8/B	1.6	6120	3330	2900	2770	2660	2660	3990	3560
	23						13480	7330	6390	6100	5860	38570	8790	7840	
	W15L	17.4	55.7	25.1	166		2.2	7380	4010	3500	3340	3210	3210	4820	4300
	32						16260	8830	7710	7360	7070	46545	10620	9470	
	W16L	441	1415	637	4223		2.8	8510	4630	4030	3850	3700	3700	5550	4960
	41						18740	10200	8880	8480	8150	53650	12220	10930	
	3.2						9200	5000	4360	4160	4000	4000	6000	5360	
						46	20260	11010	9600	9160	8810	58000	13220	11810	

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards