

# YIELDMAX



**FEATURE**

- R1-W Pattern

**BENEFIT**

- Longer tyre life

**FEATURE**

- Dual Lug angle

**BENEFIT**

- Higher traction and better stability

**FEATURE**

- Higher lug overlap

**BENEFIT**

- Enhanced road ability and load ability

**FEATURE**

- Strong & sharp shoulders

**BENEFIT**

- Better grip

**FEATURE**

- Wide open shoulders

**BENEFIT**

- Better self cleaning

**FEATURE**

- Rounded Lug Base

**BENEFIT**

- Stubble Resistance


**FEATURE**

- Steel belted radial construction

**BENEFIT**

- Protection from Punctures

## MACHINERY



### Harvester

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							Cyclic operation	
		SW	OD	Radius	mm	Speed		Speed, km/h (mph)								
		mm	mm	mm	mm	bar		Constant load								
		in	in	in	in	psi		Static	10	20	30	40	50	10	15	
800/65R32 CHO SB*	DW27B,	800	1853	830	5540	181A8/B	0.8	7640	4980	4080	3550	3320	3320	5980	5480	
	12						16830	10970	8990	7820	7310	7310	13170	12070		
	1.6						11450	7470	6130	5330	4980	4980	8960	8220		
	23						25220	16450	13500	11740	10970	10970	19740	18110		
	2						13040	8510	6970	6070	5670	5670	10210	9360		
	29						28720	18740	15350	13370	12490	12490	22490	20620		
	2.6						15200	9920	8130	7070	6610	6610	11900	10910		
	38						33480	21850	17910	15570	14560	14560	26210	24030		
	3.8						18980	12380	10150	8830	8250	8250	14850	13610		
	55						41810	27270	22360	19450	18170	18170	32710	29980		

\* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards