

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage


FEATURE

- Steel belted radial construction

BENEFIT

- Protection from Punctures

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in					static	Up to 65km/h Up to 40mph	70 43	10 6
VF 650/ 60R42 SB*	DW 21B DW 23B DW 20 (NRO)	TL	650	1913	851	5661	174D	0.8	9020	3920	3570	5490
			25.6	75.3	33.5	222.9		12	19870	8630	7860	12090
								1.2	11430	4970	4520	6960
								17	25180	10950	9960	15330
								1.6	13520	5880	5350	8230
								23	29780	12950	11780	18130
								2	15410	6700	6100	9380
				29	33940	14760	13440	20660				

* SB - Steel belted

Note:- for NRO rim please increase 0.2bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards