

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Type	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)			
			SW	OD					MIXED APPLICATION			CYCLIC*
			mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi	static	Up to 65km/h Up to 40mph	70 43	10 6
VF 650/ 65R42	DW 21B, DW 23B DW 20 (NRO)	TL	650 25.6	1913 75.3	851 33.5	5661 222.9	174D	0.8	9020	3920	3570	5490
								12	19870	8630	7860	12090
								1.2	11430	4970	4520	6960
								17	25180	10950	9960	15330
								1.6	13520	5880	5350	8230
								23	29780	12950	11780	18130
								2	15410	6700	6100	9380
								29	33940	14760	13440	20660

Note:- for NRO rim please increase 0.2bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards