

# FARMAX HPT



**FEATURE**

Lug Tip Step

**BENEFIT**

Increase the grip and reducing the tractor slip

**FEATURE**

Lug base tie bar

**BENEFIT**

Additional support to lugs and also helps to remove mud from lugs

**FEATURE**

Extra wide tread

**BENEFIT**

Wider footprint provides increased stability

**FEATURE**

50° lug angle at centre

**BENEFIT**

Smoother road driving comfort, less noise and vibration

**FEATURE**

Rounder shoulder

**BENEFIT**

Provides less soil damage  
Better Grip


**FEATURE**

Deeper Tread Depths

**BENEFIT**

Provides improved traction and gripping power longer tire life

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Tractor application							
								Static	10	20	30	40	50	65	
710/70R42	DW23B, DW25B	716	2061	932	6151	173D/ 176A8	0.8	7870	5130	4210	3930	3740	3590	3420	
		28.2	81.1	36.7	242.2		12	17330	11300	9270	8660	8240	7910	7530	
							1.2	9980	6510	5340	4990	4750	4560	4340	
							17	21980	14340	11760	10990	10460	10040	9560	
							1.6	11800	7700	6310	5900	5620	5390	5130	
							23	25990	16960	13900	13000	12380	11870	11300	
							2	13430	8760	7180	6720	6390	6130	5840	
							29	29580	19300	15810	14800	14070	13500	12860	
							2.4	14950	9750	8400	7480	7120	6830	6500	
				35	32930	21480	18500	16480	15680	15040	14320				

All tires confirms ETRTO T&RA & STRO standards