

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Sprayer

Size	Rim	Infl tire dimension		Loaded Static Radius	Rolling Circumference	Load Index	Infl.Press	Recommend Load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
380/105R50	W12 W13	400	2050	952	6144	168D/ 171A8	0.8	2380	3110	2450	2270	2170	2070	1880
							12	5240	6850	5400	5000	4780	4560	4140
							1.6	3570	4650	3670	3390	3260	3100	2820
							23	7860	10240	8080	7470	7180	6830	6210
							2.4	4520	5900	4660	4300	4130	3930	3580
							35	9960	13000	10260	9470	9100	8660	7890
							3.6	5730	7470	5900	5450	5230	4980	4530
							52	12620	16450	13000	12000	11520	10970	9980
							4.0	6100	7950	6280	5800	5570	5300	4820
							58	13440	17510	13830	12780	12270	11670	10620
							4.4	6440	8400	6640	6130	5880	5600	5100
							64	14190	18500	14630	13500	12950	12330	11230

All tires confirms ETRTO T&RA & STRO standards