

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
650/ 65R42	158D	TL	DW20BL W18L	645	1939	896	5854 230.5	0.8	3250	3350	3100	2970	2830	1	4810	4390
								12	7160	7380	6830	6540	6230	15	10590	9670
								1.0	3710	3830	3540	3390	3230	1	5490	5010
								15	8170	8440	7800	7470	7110	18	12090	11040
								1.3	4320	4460	4120	3950	3760	2	6390	5830
								19	9520	9820	9070	8700	8280	24	14070	12840
								1.6	4890	5040	4650	4460	4250	2	7230	6590
								23	10770	11100	10240	9820	9360	29	15930	14520

All tires confirms ETRTO T&RA & STRO standards