

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction


**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
IF600/ 70R34	DW20L DW21L	603 23.7	1704 67.1	768 30.3	5086 200.2	160D	0.8	6950	3780	3100	3020	2750	1.6	4230	
							12	15310	8330	6830	6650	6060	23	9320	
							1	7910	4300	3530	3440	3130	1.8	4820	
							15	17420	9470	7780	7580	6890	26	10620	
							1.2	8810	4790	3930	3830	3490	2	5360	
							17	19410	10550	8660	8440	7690	29	11810	
							1.4	9640	5240	4290	4190	3810	2.2	5870	
							20	21230	11540	9450	9230	8390	32	12930	
							1.6	10420	5660	4640	4530	4120	2.4	6340	
23	22950	12470	10220	9980	9070	35	13960								

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards