

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
IF600/ 70R34	DW20L DW21L	603 23.7	1704 67.1	768 30.3	5086 200.2	167D	0.8	6580	3580	2930	2860	2600	1.6	4000	
							12	14490	7890	6450	6300	5730	23	8810	
							1.2	8350	4540	3720	3630	3300	2	5080	
							17	18390	10000	8190	8000	7270	29	11190	
							1.6	9890	5380	4410	4300	3910	2.4	6020	
							23	21780	11850	9710	9470	8610	35	13260	
							2	11270	6130	5020	4900	4460	2.8	6860	
							29	24820	13500	11060	10790	9820	41	15110	
							2.4	12540	6810	5590	5450	4960	3.2	7630	
35	27620	15000	12310	12000	10930	46	16810								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards