

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION				CYCLIC*			
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar	static	10	20	25 to 65
IF650/ 60R34	DW23B	650 25.6	1644 64.7	735 28.9	4855 191.1	159D	0.8	6720	3650	2990	2920	2660	1.6	4090	
							12	14800	8040	6590	6430	5860	23	9010	
							1.0	7660	4160	3410	3330	3030	1.8	4660	
							15	16870	9160	7510	7330	6670	26	10260	
							1.2	8510	4630	3790	3700	3370	2	5180	
							17	18740	10200	8350	8150	7420	29	11410	
							1.6	10060	5470	4480	4375	3980	2.4	6130	
							23	22160	12050	9870	9640	8770	35	13500	

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards