

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF600/ 65R28	DW20L DW21L	597 23.5	1491 58.7	645 25.4	4403 173.3	163D	0.8	6580	3060	2860	2860	2600	1.6	4000	
							12	14490	6740	6300	6300	5730	23	8810	
							1.2	8330	3880	3620	3620	3290	2	5070	
							17	18350	8550	7970	7970	7250	29	11170	
							1.4	9110	4240	3960	3960	3600	2.2	5540	
							20	20070	9340	8720	8720	7930	32	12200	
							1.6	9840	4590	4280	4280	3890	2.4	5990	
							23	21670	10110	9430	9430	8570	35	13190	
							2	11210	5220	4880	4875	4440	2.8	6830	
29	24690	11500	10750	10740	9780	41	15040								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards